

Fairpoxy top casting resin A

Product description

Fairpoxy top casting resin A is a formulated, water white, low viscosity epoxy resin, specifically designed for the production of decorative tabletops, renovation of kitchen worktops, decoupage and other hobby applications.

Fairpoxy top casting resin A is designed for use with Fairpoxy top casting hardener B in a convenient 2:1 by volume mix ratio (resin: hardener).

Fairpoxy top casting resin A can be pigmented using suitable epoxy based pigment paste. After cure with the recommended curing agents in the recommended mix ratio the system shows high transparency and better resistance to discoloration on ageing than conventional epoxy resin systems.

Product characteristics

Viscosity @25°C : 420 – 960 mPa.s Color : Water White Solids content : 100 % m/m Epoxide Equivalent Weight : 190 – 210 g/Eq

The epoxy resin curing agent system Fairpoxy top casting has a certified bio carbon content of minimum 25% when mixed in the recommended ratio.

The system will be certified by the US Department of Agriculture (USDA) under the Biopreferred programme (www.biopreferred.gov/BioPreferred) in the near future.

Storage and handling

The product should be stored in a dry place, at room temperature, preferably above 10°C.

Shelf-life: beyond 2 years, in original sealed containers.

More information about safe handling of this product can be found in the safety data sheet.

Disclaimer: this information is provided for general information purposes only and is believed to be accurate as of the date hereof; however Fairpoxy does not make any warranties or representations of any kind regarding the information herein and no liabilities, including those for patent rights, can be derived from it. It is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use.